



# APPLICATION and PERFORMANCE SPECIFICATION

## ACT1S26RS120N

- Line Voltage: 120V 60Hz
- Series Lamp Operation
- Rapid Start
- Lamp End of Life Protection

Lamp Type			Min. Start Temp. (F/C)	V <sub>in</sub> (V)	I <sub>in</sub> (A)	P <sub>in</sub> (W)	ATHD ≤%	PF ≥	CF ≤	BF	BEF
Type	No.	Watts									
* CFQ26W/G24q-3	1	26	0/-18	120	0.43	26	150	0.5	1.7	0.88	3.26
FC8T9	1	22	0/-18	120	0.31	22	150	0.5	1.7	0.90	4.13

Note: Application and Performance Specification Information Subject to Change without Notification.

### Performance

- Meets ANSI Standard C62.41-2002
- Meets FCC 18 CONSUMER Limits

### Safety

- No PCB's
- UL & cUL listed (Class P, Type 1 Outdoor)
- OCV 300V
- TYPE HL

### Application

- Maximum Ambient Temperature: 131°F, 55°C
- Sound Rated: A
- Maximum case temperature T<sub>c</sub>: 167°F, 75°C
- Starting time: 0.5s < t < 1s

### Physical Parameters

- Length 3.9" (98mm)
- Width 2.0" (51mm)
- Height 1.2" (30mm)
- Weight 0.6 lbs

### Lead Length

- White/Black 12" ± 1"
- Red/Blue 12" ± 1"

