



APPLICATION and PERFORMANCE SPECIFICATION

ACT2S40PSUNV

- Line Voltage:120-277V 50/60Hz
- Series Lamp Operation
- Type CC
- Program Start
- Active Power Factor Correction

Lamp Type			Min. Start Temp. (F/C)	Vin (V)	Iin (A)	Pin (W)	ATHD ≤%	PF ≥	CF ≤	BF	BEF
Type	No.	Watts									
F40T8	2	40	-20/-30	120	0.88	105	10	0.99	1.7	1.35	1.29
F40T8	2	40	-20/-30	277	0.37	103	10	0.96	1.7	1.35	1.29
F40T8	1	40	-20/-30	120	0.43	52	5.2	0.99	1.7	1.33	2.56
F40T8	1	40	-20/-30	277	0.21	52	8.1	0.9	1.7	1.33	2.56
F32T8	2	32	-20/-30	120	0.68	82	3.8	0.99	1.7	1.33	1.63
F32T8	2	32	-20/-30	277	0.31	81	5.5	0.95	1.7	1.33	1.63

Note: Application and Performance Specification Information Subject to Change without Notification.

Performance

- Meets ANSI Standard C82.11-2002
- Meets ANSI Standard C62.41-2002
- Meets FCC 18 Non CONSUMER Limits

Application

- Maximum Ambient Temperature: 131°F,55°C
- Remote Mounting: 6 ft. max. Lead length, 18AWG
- Sound Rated: A
- Maximum case temperature Tc: 194°F,90°C

Safety

- No PCB's, Type HL
- UL & cUL listed (Class P, Type 1 Outdoor)
- OCV 600V

Physical Parameters

- Length * Width * Height 9.75 " *1.6 " *1.1 "
- Mounting 8.9"
- Weight 1.10 lbs
- White, Black 25"(±1")
- Orange 20"(±1")
- Brown 20"(±1")
- Yellow 20"(±1")
- Red/ Blue 20"(±1")

